










# CANILO

# oktalite

[www.oktalite.com/canilo-p](http://www.oktalite.com/canilo-p)

Type of luminaire	suspended luminaire
Application areas	Accent lighting
Pan/tilt range	fixed
Mounting	3P Power Track, recessed, Surface mounted
Ceiling thickness	1 - 25 mm
Lighting technology	LED
LED Luminous Flux Class	2000 lm - 3000 lm
Light colour White	2700 K, 3000 K, 3000 K - Efficient White, 3000 K - Brilliant Colour, 3500 K, 4000 K, 4000 K - Efficient Cool
Cooling	passive
Supply unit	Driver separate / integrated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	structure powder-coated
Suspension length	1500mm, 3000mm
Nominal voltage	220 - 240 V, 50/60Hz
Lighting controls	on request
Weight	Approx. 2.0 kg
Components	 Luminaire housing  Optic  Supply unit
Test seal	   



Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15



## CANILO

## oktalite

Mounting  
Supply unitSurface mounted H11  
integrated

LED Luminous Flux Class	Light colour	CRI R <sub>a</sub>	system luminous flux*	System performance	Suspension length	Order number		
						white	silver	black
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	1500mm	10226671	10226672	10226673
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	3000mm	10226674	10226675	10226676
2000 lm	3000 K - Brilliant Colour	97	1800 lm	22 W	1500mm	10226677	10226678	10226679
2000 lm	3000 K - Brilliant Colour	97	1800 lm	23 W	3000mm	10226680	10226681	10226682
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	1500mm	10249595	10249596	10249597
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	3000mm	10249598	10249599	10249600
3000 lm	2700 K	81	2710 lm	24 W	1500mm	10226683	10226684	10226685
3000 lm	2700 K	81	2710 lm	25 W	3000mm	10226686	10226687	10226688
3000 lm	3000 K	83	2825 lm	24 W	1500mm	10226689	10226690	10226691
3000 lm	3000 K	83	2825 lm	25 W	3000mm	10226692	10226693	10226694
3000 lm	3000 K - Efficient White	94	2785 lm	29 W	1500mm	10226695	10226696	10226697
3000 lm	3000 K - Efficient White	94	2785 lm	30 W	3000mm	10226698	10226699	10226700
3000 lm	3500 K	84	2880 lm	24 W	1500mm	10226707	10226708	10226709
3000 lm	3500 K	84	2880 lm	25 W	3000mm	10226710	10226711	10226712
3000 lm	4000 K	83	2935 lm	24 W	1500mm	10226713	10226714	10226715
3000 lm	4000 K	83	2935 lm	25 W	3000mm	10226716	10226717	10226718
3000 lm	4000 K - Efficient Cool	91	2980 lm	29 W	1500mm	10249601	10249602	10249603
3000 lm	4000 K - Efficient Cool	91	2980 lm	30 W	3000mm	10249604	10249605	10249606


Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15



## CANILO

## oktalite

Mounting 3P Power Track H11  
Supply unit integrated



LED Luminous Flux Class	Light colour	CRI R <sub>a</sub>	system luminous flux*	System performance	Suspension length	Order number		
						white	silver	black
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	1500mm	10226623	10226624	10226625
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	3000mm	10226626	10226627	10226628
2000 lm	3000 K - Brilliant Colour	97	1800 lm	22 W	1500mm	10226629	10226630	10226631
2000 lm	3000 K - Brilliant Colour	97	1800 lm	23 W	3000mm	10226632	10226633	10226634
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	1500mm	10249577	10249578	10249579
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	3000mm	10249580	10249581	10249582
3000 lm	2700 K	81	2710 lm	24 W	1500mm	10226635	10226636	10226637
3000 lm	2700 K	81	2710 lm	25 W	3000mm	10226638	10226639	10226640
3000 lm	3000 K	83	2825 lm	24 W	1500mm	10226641	10226642	10226643
3000 lm	3000 K	83	2825 lm	25 W	3000mm	10226644	10226645	10226646
3000 lm	3000 K - Efficient White	94	2785 lm	29 W	1500mm	10226647	10226648	10226649
3000 lm	3000 K - Efficient White	94	2785 lm	30 W	3000mm	10226650	10226651	10226652
3000 lm	3500 K	84	2880 lm	24 W	1500mm	10226659	10226660	10226661
3000 lm	3500 K	84	2880 lm	25 W	3000mm	10226662	10226663	10226664
3000 lm	4000 K	83	2935 lm	24 W	1500mm	10226665	10226666	10226667
3000 lm	4000 K	83	2935 lm	25 W	3000mm	10226668	10226669	10226670
3000 lm	4000 K - Efficient Cool	91	2980 lm	29 W	1500mm	10249583	10249584	10249585
3000 lm	4000 K - Efficient Cool	91	2980 lm	30 W	3000mm	10249586	10249587	10249588

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15




Luminaire housing - LED

# CANILO

# oktalite

Mounting recessed H12 (Ø 130mm)  
Supply unit separate



LED Luminous Flux Class	Light colour	CRI R <sub>a</sub>	system luminous flux*	System performance	Suspension length	Order number		
						white	silver	black
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	1500mm	10226737	10226738	10226739
2000 lm	3000 K - Efficient White	94	1910 lm	18 W	3000mm	10226740	10226741	10226742
2000 lm	3000 K - Brilliant Colour	97	1800 lm	22 W	1500mm	10226719	10226720	10226721
2000 lm	3000 K - Brilliant Colour	97	1800 lm	23 W	3000mm	10226722	10226723	10226724
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	1500mm	10249613	10249614	10249615
2000 lm	4000 K - Efficient Cool	91	2040 lm	18 W	3000mm	10249616	10249617	10249618
3000 lm	2700 K	81	2710 lm	24 W	1500mm	10226725	10226726	10226727
3000 lm	2700 K	81	2710 lm	25 W	3000mm	10226728	10226729	10226730
3000 lm	3000 K	83	2825 lm	24 W	1500mm	10226731	10226732	10226733
3000 lm	3000 K	83	2825 lm	25 W	3000mm	10226734	10226735	10226736
3000 lm	3000 K - Efficient White	94	2785 lm	29 W	1500mm	10226737	10226738	10226739
3000 lm	3000 K - Efficient White	94	2785 lm	30 W	3000mm	10226740	10226741	10226742
3000 lm	3500 K	84	2880 lm	24 W	1500mm	10226743	10226744	10226745
3000 lm	3500 K	84	2880 lm	25 W	3000mm	10226746	10226747	10226748
3000 lm	4000 K	83	2935 lm	24 W	1500mm	10226749	10226750	10226751
3000 lm	4000 K	83	2935 lm	25 W	3000mm	10226752	10226753	10226754
3000 lm	4000 K - Efficient Cool	91	2980 lm	29 W	1500mm	10249613	10249614	10249615
3000 lm	4000 K - Efficient Cool	91	2980 lm	30 W	3000mm	10249616	10249617	10249618

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15

\* System luminous flux based on medium flood reflector.



Efficient White:  $R_9 = 75$ ,  $R_i = 91$ ,  $R_g = 102$




Brilliant Colour:  $R_9 = 94$ ,  $R_i = 95$ ,  $R_g = 104$


Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of  $\pm 10\%$ . Min CRI Ra:  $>80 / >90$  · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15


# Optic 85 - LED

# oktalite

Optic 3D faceted reflectors  
Type interchangeable reflector system

Beam angle				Cover	LOR	Order number																		
Spot						white	silver	black																
<b>Optik 85 - SP</b>				without	82 %	-	-	10183944																
<table border="1"> <thead> <tr> <th>Höhe [m]</th> <th>KegelØ [cm]</th> <th>E(0°) [lx/klm]</th> <th>E(C0) [lx/klm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>26</td> <td>5755</td> <td>2841</td> </tr> <tr> <td>2</td> <td>52</td> <td>1439</td> <td>710</td> </tr> <tr> <td>3</td> <td>78</td> <td>639</td> <td>316</td> </tr> </tbody> </table>				Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]	1	26	5755	2841	2	52	1439	710	3	78	639	316	clear	78 %	-	-	10184576
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]																					
1	26	5755	2841																					
2	52	1439	710																					
3	78	639	316																					
																								

Beam angle				Cover	LOR	Order number																		
Medium Flood						white	silver	black																
<b>Optik 85 - MF</b>				without	83 %	-	-	10183959																
<table border="1"> <thead> <tr> <th>Höhe [m]</th> <th>KegelØ [cm]</th> <th>E(0°) [lx/klm]</th> <th>E(C0) [lx/klm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>45</td> <td>2845</td> <td>1321</td> </tr> <tr> <td>2</td> <td>91</td> <td>711</td> <td>330</td> </tr> <tr> <td>3</td> <td>136</td> <td>316</td> <td>147</td> </tr> </tbody> </table>				Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]	1	45	2845	1321	2	91	711	330	3	136	316	147	clear	79 %	-	-	10184577
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]																					
1	45	2845	1321																					
2	91	711	330																					
3	136	316	147																					
																								


Beam angle				Cover	LOR	Order number																		
Flood						white	silver	black																
<b>Optik 85 - FL</b>				without	82 %	-	-	10183953																
<table border="1"> <thead> <tr> <th>Höhe [m]</th> <th>KegelØ [cm]</th> <th>E(0°) [lx/klm]</th> <th>E(C0) [lx/klm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>66</td> <td>1941</td> <td>832</td> </tr> <tr> <td>2</td> <td>132</td> <td>485</td> <td>208</td> </tr> <tr> <td>3</td> <td>197</td> <td>216</td> <td>92</td> </tr> </tbody> </table>				Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]	1	66	1941	832	2	132	485	208	3	197	216	92	clear	78 %	-	-	10184578
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]																					
1	66	1941	832																					
2	132	485	208																					
3	197	216	92																					
																								


Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15

# Optic 85 - LED

# oktalite

Optic 3D faceted reflectors  
 Type interchangeable reflector system

Beam angle				Cover	LOR	Order number																							
Wide Flood						white	silver	black																					
<b>Optik 85 - WFL</b> <table border="1"> <thead> <tr> <th>Höhe [m]</th> <th>KegelØ [cm]</th> <th>E(0°) [lx/klm]</th> <th>E(C0) [lx/klm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>83</td> <td>1522</td> <td>601</td> </tr> <tr> <td>2</td> <td>167</td> <td>381</td> <td>150</td> </tr> <tr> <td>3</td> <td>250</td> <td>169</td> <td>67</td> </tr> </tbody> </table>				Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]	1	83	1522	601	2	167	381	150	3	250	169	67						without	82 %	-	-	10183954
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]																										
1	83	1522	601																										
2	167	381	150																										
3	250	169	67																										
				clear	78 %	-	-	10184579																					

Beam angle				Cover	LOR	Order number																							
Very Wide Flood						white	silver	black																					
<b>Optik 85 - VFL</b> <table border="1"> <thead> <tr> <th>Höhe [m]</th> <th>KegelØ [cm]</th> <th>E(0°) [lx/klm]</th> <th>E(C0) [lx/klm]</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>111</td> <td>1067</td> <td>360</td> </tr> <tr> <td>2</td> <td>223</td> <td>267</td> <td>90</td> </tr> <tr> <td>3</td> <td>334</td> <td>119</td> <td>40</td> </tr> </tbody> </table>				Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]	1	111	1067	360	2	223	267	90	3	334	119	40						without	82 %	-	-	10183955
Höhe [m]	KegelØ [cm]	E(0°) [lx/klm]	E(C0) [lx/klm]																										
1	111	1067	360																										
2	223	267	90																										
3	334	119	40																										
				clear	78 %	-	-	10184580																					

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15



Supply unit - LED

## Driver

# oktalite

Version	Independent control gear
Connection type	Pre-wired plug-in connectivity
Mains connection	GST 18i3
Cable length secondary	400 mm
Nominal voltage	220 - 240 V, 50/60Hz
protection	IP20
protection class	I, II
Lighting controls	on request
Lighting technology	LED

Lighting technology	Luminaire connection	Output	System performance	max. luminaires B16	Order number
LED	RNV	450 mA	18 W	49	10211947
LED	RNV	550 mA	22 W	27	10264893
LED	RNV	550 mA	23 W	27	10264893
LED	RNV	600 mA	24 W	25	10211950
LED	RNV	600 mA	25 W	25	10211950
LED	RNV	700 mA	29 W	25	10211952
LED	RNV	700 mA	30 W	25	10211952

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. The Single Lighting Regulation (SLR) documentation can be found in our download area. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T 49 221 59767-0 · F 49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2023-05-15